

DG SET SPECIFICATION & SCOPE

SUPERNOVA Genset, Model SV 200, powered by heavy duty Industrial, internal combustion Diesel Engine coupled with A.C. Generator, so as to generate 200 KVA / 160 KW , 415 V, 3 Phase, 0.8 pf, 50 Hz at standard reference conditions & further as per following :-

DIESEL ENGINE :

Imported **VOLVO PENTA** 4-stroke, vertical, inline 6 (six) Cylinder, Water-Cooled, Turbocharged Diesel Engine Model TAD 733GE developing 246 BHP at 1500 rpm prime-power rating as per ISO-3046, BS-5514 with a provision of 10% overload for 1 hour in any 12 hour running under std. reference conditions. Governing performance in accordance with class-A1 as per ISO-3046, BS-5514, DIN 6271 and can be operated upto 1000 M. Altitude and 40 Deg.C. Ambient Air Temperature WITHOUT ANY DERATION.

The Engine shall be complete with the following:

- Lubrication System
- Fuel System
- Intake & Exhaust System
- Cooling System
- Starting System
- Switches & Sensors
- Engine Control Panel
 - Instruments & Monitors
 - Protections & Annunciations

Genset Model	SV 200
Engine Model	TAD 733GE
Type	4 Cycle, Radiator cooled, 1500 RPM
No. of Cylinder & Arrangement	6 Nos IN-LINE
Governor	Electronic
Bore x Stroke (mm x mm)	108 x 130
Compression Ratio	18 : 1
Starting	24 V DC Electric Starting
Battery	2 Nos. x 120 AH
Fuel Tank	8 hours running capacity.
Engine Water incl. Radiator	37.1 Litres
Sump Capacity	31 Litres
Lub. Oil Consumption (Lit / h)	0.08

A.C.GENERATOR:

STAMFORD/CROMPTON make Industrial A.C.Generator, Brushless, synchronous, self excited, self regulated, Screen Protected Drip Proof, 200 KVA / 160 KW, 3 phase,

4 wire, 415V, 0.8 p.f., 1500 rpm, 50 Hz, Enclosure - IP23, Class of Insulation 'H', Voltage regulation of (+/-)1%. It shall be Horizontal foot mounted single bearing type confirming to BS5000, IS4722.

MOUNTING:

The engine and A.C. Generator described above shall be directly coupled, aligned and mounted on rigid M.S. Fabricated Base Frame.

CONTROL PANEL:

The Control panel shall be designed fitted with Imported Microprocessor based, State-of-art, latest technology ' D.G. Set -Controller' for complete control of DG Set which comprises of Control, Monitoring & Protection of Engine & Alternator.

The Panel shall be fabricated from processed 16 gauges CRCA Sheet Metal, suitable for outdoor/ indoor application.

The panel shall be powder coated/ painted after the seven tank process of degreasing, de-rusting. The Doors and covers are provided with Neoprene Gasket to ensure dust & vermin proof as per IP 52. The gland plate/s is provided at bottom for termination of input and output Power / control Cable.

Options :

AMF panel (Auto Start but without Change-over facility)

AMF - Auto Start, Auto change-over panel.

Auto Start, Auto Synchronizing, Auto load sharing panels.

ACOUSTIC ENCLOSURE. (Model SW20VCS0200.O.P)

- A thoughtfully crafted art-piece.
- Enables reduction of 25dbA, thus at 1 Mtr. Distance under free field conditions, it measures 75 dbA.
- Structure/Profile made out of high quality CRCA Sheet Steel
- Roof, Side wall, integral partition and doors are all sandwich design made out of high quality CRCA Sheet steel.
- Is natural cooled and maintain t (temperature difference with Air ambient) of 5 – 7 Cent. If need arises articulated ventilation are also considered.
- Sound absorption material is Rock Wool of relevant thickness and density.
- Provide sufficient access for maintenance work.
- Control panel is mounted inside the Enclosure (except Synchronizing panel)
- Fuel tank of 8 hours running capacity with arrangement of e-filling, Air-vent, Drain, Supply & return connection provided.
- Arrangement of Power cable connection
- Residential exhaust silencers
- Suction Louvers
- Discharge Louvers

- Openable and lockable doors
- Interior lighting arrangement

Canopy Dimension: L x W x H (3624.5 x 1600 x 1760)

PERIPHERALS:

- M.S. Fabricated Fuel Storage Day Tank with Level Indicator for 8 hours operation capacity.
- Heavy Duty Industrial Silencer
- Exhaust Flexible expansion Pipe
- Fuel Pre-filter with Element & Water Separator
- Dry Batteries with Leads. (Qty. 2 Nos., 150 AH)

DOCUMENTS:

- D.G.Set Test Certificate
- Engine/A.C. Generator
 - O & M Manuals
 - Parts Catalogue
- Alternator Test Certificate